



Preliminary Technical Program

Presentation Times as of July 17, 2017

Monday, September 11

8:15 AM	Keynote Address	Page 2
9:00 AM	Vacuum Arc Remelting	Page 2
1:30 PM	Electroslag Remelting I	Page 3
5:15 PM	Poster Session	Page 4

Tuesday, September 12

8:15 AM	Static Casting	Page 6
11:00 AM	Continuous Casting and Melting	Page 7
1:30 PM	Electroslag Remelting II	Page 7

Wednesday, September 13

8:15 AM	Vacuum Induction Melting	Page 8
9:20 AM	Inclusions	Page 9
11:00 AM	Titanium Processing	Page 9

Keynote Address

Monday AM
September 11, 2017

Room: Grand Ballroom
Location: The Hyatt at the Bellevue

8:15 AM Introductory Comments

8:20 AM Keynote

Title to be announced.: *Mary Lee Gambone*¹; ¹Rolls-Royce North America
To be announced.

Vacuum Arc Remelting

Monday AM
September 11, 2017

Room: Grand Ballroom
Location: The Hyatt at the Bellevue

9:00 AM

Numerical Simulation of the Vacuum Arc Remelting Process with ANSYS Fluent: *Moritz Eickhoff*¹; Antje Rückert¹; Herbert Pfeifer¹; Jürgen Tewes²; Thorsten Hoffmann²; Jutta Klöwer²; ¹RWTH Aachen University; ²VDM Metals GmbH

The vacuum arc remelting process is used to improve both cleanliness and a controlled grain structure for high potential metals like Nickel based superalloys. A self-consuming electrode is continuously molten by electric arcs sparkling between electrode tip and metal pool. The liquid droplets fall from the electrode to the metal pool and resolidify because of the water cooled copper mould. The numerical simulation is done with ANSYS Fluent in combination with user-defined functions and coupling with ANSYS APDL. ANSYS Fluent models the flow field and temperature distribution in the ingot. The user-defined functions offer the possibility to model different heat transfer mechanisms in detail. The current density and Lorentz forces are calculated with ANSYS APDL and implemented as source terms. The model can be validated by the “macroscopic texture examination” an in-house development to determine dendrite growth directions on huge metallurgical samples.

9:20 AM

Application of a Photodiode Based Instrumentation to Study the Dynamics of the Electric Arc during Industrial Vacuum Arc Remelting of a Ti Alloy: *Pierre-Olivier Delzant*¹; Pierre Chapelle¹; Alain Jardy¹; Julien Jourdan¹; Julien Jourdan²; Yvon Millet²; ¹Institut Jean Lamour; ²TIMET Savoie

We present an experimental investigation of the dynamics of the electric arc during industrial VAR melt of a Ti64 electrode that is based on the analysis of the luminous emission of the arc. The latter was recorded using four photodiodes placed inside the furnace above the annular gap between the consumable electrode and the crucible. From the quantitative comparison of the signals of the four photodiodes, we were able to determine the location of the arc luminosity centroid and to follow its motion as a function of time. A periodic (with period of the order of several tens of seconds) and asymmetrical evolution of the arc centroid position was observed with a strong correlation between the centroid motion and the evolution of the stirring current. Three different patterns of the arc centroid motion were identified during the melt.

9:40 AM

The Influence of Magnetic Stirring on the Measured Arc Behaviour during VAR of an Alpha-Ti Alloy: Bindu Nair¹; Yvon Millet²; Julien Jourdan²; *R Mark Ward*¹; ¹University of Birmingham; ²TIMET

The period and magnitude of the solenoid field used in the VAR of an ingot of an alpha-Ti alloy were varied over the course of the melt. 3-axis magnetic flux density sensors were placed around the outside of the furnace, and the measurements were interpreted to infer the location of the arc in 3d at each time instant. The results were compared with video and other furnace parameters which were recorded simultaneously, and the effects of the solenoid are presented and discussed. Complex behaviour was observed, with the arc centre moving freely in some cases and being confined to regions in others.

10:00 AM Break

10:40 AM

Exploration of VAR Argon-Filling Process for 300M Steel: Yuchun Zhang¹; Rui Wang¹; Xianchao Bai¹; Xuehui Liu¹; Zhouhua Jiang²; ¹Fushun Special Steel; ²Northeastern University

The experimental research on argon filling during vacuum arc remelting (VAR) of 300M has been performed. The results showed that there was a significant influence on VAR process and the ingot quality. In the process of VAR, the yield of manganese increased when the pressure of argon filling increased. When the argon pressure was less than 50pa, the arc was stable, the pool was active, the yield of Mn in the ingot increased significantly in comparing with traditional process, the Mn difference in different positions of the same ingot decreased a lot, and the chemical composition is uniform. The metallurgical quality of the steel bars totally conforms to current technical specification.

11:00 AM

Investigation into the Spatio-temporal Properties of Arcs in Vacuum Arc Remelting Furnaces: *Matthew Cibula*¹; Rigel Woodside¹; Paul King¹; ¹Ampere Scientific

The behavior of vacuum arcs during VAR processing is known to impact product yield and contribute to ingot defects. Ampere Scientific's VARmetric system has demonstrated non-invasive detection of the spatio-temporal properties of vacuum arcs, including the detection of side-arcing conditions, by utilizing measurements of the magnetic field external to the furnace. Here we present an analysis of spatio-temporal arc distributions measured by VARmetric on a production VAR furnace. Analysis of the arc over different timescales provides new insights into the operating characteristics of VAR furnaces, and on how power is transferred to the molten pool. For example, even under similar steady state operating conditions within a given melt, we have identified significantly different arc distributions, information that may be useful in further understanding the characteristics of the molten metal pool.

11:20 AM

Inclusion Transformation in Vacuum Arc Remelting: *George Shannon*¹; ¹Carpenter Latrobe Specialty Steel

Inclusion content in a VAR electrode and the resulting ingot of a low alloy structural steel was analyzed using an automated scanning electron microscope. Center, mid-radius, and edge samples were examined from both the top and bottom ends in each case. It was observed that a drastic reduction in inclusion content occurs, however, this reduction does not place consistently between inclusion-forming elements. Volatile elements such as magnesium and calcium are removed more so than very stable oxide-forming elements such as aluminum. Center and mid-radius samples were found to be cleaner than edge samples in both electrode and ingot cases. Inclusion sources in the teeming setup were identified and eliminated; this was based on electrode analysis, not ingot analysis, indicating that transformations during VAR may disguise inclusion origins.

11:40 AM

Titanium Melting with High Power Plasma Torch: *Henrik Franz*¹; Ulrich Biebricher¹; Radisav Dzombic¹; Dieter Kaufhold¹; Christoph Morche¹; Robert Link¹; Sergejs Spicans¹; ¹ALD Vacuum Technologies GmbH

In this paper experimental results of melting tests with a newly-developed high power plasma torch are presented. Current-Voltage characteristics of the plasma torch and melting behavior at various operation pressures with different plasma gases (Helium, Argon) will be explained in detail. Most of those tests were performed in a water cooled copper hearth with Titanium as feedstock material. For comparison of heat distribution, and in order to reveal performance characteristics of the torch, tests with Graphite were conducted. With torch currents ranging from 2 to 6 kA, a broad operation window was examined and it will be shown how various operation parameters (e.g. torch standoff distance, torch current) impact on melting efficiency. Results from pool depth measurements at various torch currents and results of an online gas analysis performed by an RGA during those melting tests will also be presented.

Electroslag Remelting I

Monday PM
September 11, 2017

Room: Grand Ballroom
Location: The Hyatt at the Bellevue

1:30 PM

Management of Physical and Structural Homogeneity of Hollow Ingot by Electro Slag Remelting: Leonid Levkov¹; Vladimir Dub¹; Michael Kisselman¹; Ivan Ivanov¹; Dmitry Shurygin¹; ¹Public corporation Scientific and Production Association (CNIITMASH)

The results of theoretical and experimental studies that show the possibility of intensity control of heat transfer and rate of crystallization during the hollow ingots formation by ESR are presented. Development conditions of physical and structural heterogeneity in hollow ingots from alloyed steels are defined. Methods of management of these types of inhomogeneities in case of mutual moving ingot, electrode, crystallizer and using a low frequency AC are developed. The mathematical model of solidification process hollow ingots is offered, boundary conditions are defined. Experimentally confirmed adequacy of model for quality prediction of ingots. Results of development are used for hollow ESR ingots with an outer diameter 275-950mm at wall thickness up to 120mm, up to 7200mm long. It's shown that properties of metal completely correspond and even exceed requirements to pipes for thermal and nuclear power plants. That allows using these products in a cast condition.

1:50 PM

Temperature Distribution in ESR Short Collar Mold: Harald Scholz¹; Henrik Franz¹; Ulrich Biebricher¹; ¹ALD Vacuum Technologies

A crucial requirement for automated ingot withdrawal in ESR is a reliable level control of the slag pool within the mold. This paper describes how temperature measurement of the mold can be useful to learn about slag behavior underneath the electrode and top of the melt pool. In addition the withdrawal rates of the ingot can be controlled, thereby maintaining constant heat transfer rates in an industrial ESR furnace. The control of the temperature distribution in the mold wall helps to gain information on slag skin thickness, slag height and slag behavior on top of the ingot. According to the temperature measurements conclusions can be drawn on the process stability. The new additional feature on temperature control technology allows an insight into the thermal process of the refining slag and forming ingot.

2:10 PM

The High Temperature Flexural Strength of Slag Skin in Electroslag Remelting Withdrawing Process: Ximin ZANG¹; Wanming LI¹; Xin DENG¹; Zhouhua JIANG²; Jianfei Ren¹; ¹University of Science and Technology Liaoning; ²Northeastern University

The slag skin is stretched and pressed at slag-metal interface in electroslag remelting withdrawing (ESRW) process. Slag skin cracking is one of the important reasons that lead to molten slag and steel leakage. It is crucial to study the physicochemical prosperities of slags for obtaining high quality and smooth surface of ingot. The slag's melting temperature and viscosity were concerned in traditional ESR. In this paper, slag skin flexural strength test at a high temperature was carried out for three typical slags, which were 70%CaF₂+30%Al₂O₃, 60%CaF₂+20%Al₂O₃+20%CaO and 50%CaF₂+20%Al₂O₃+20%CaO+7%SiO₂+3%MgO. The slag was remelted into 40×40×160 mm sample bars, and the tests of bending strength were performed at 1000 °C, 1050 °C, 1100 °C, 1150 °C, and 1200 °C. The experimental results showed that the slag skin strength depends on mineral constituents and distribution in slag skin. High melting point, hardness mineral phase dispersion distribution was beneficial to improve the slag skin strength.

2:30 PM

Effect of Impurities on Melting Point of ESR Fluxes: Krzysztof Wroblewski¹; Carol Steinhäuser¹; James Fraley¹; Jerry Fields¹; Brent DiBiaso¹; Stuart Rudoler¹; ¹American Flux & Metal LLC

Several commercial models are capable of calculating reliable values of the liquidus temperature for multi-component fluxes. However, it is difficult to calculate such values over wide ranges of compositions, so several empirical equations are also being used for the estimation of both solidus and liquidus points, with Shridar and Mills model being one of the most popular in the field of ESR. In real world, ESR flux contains

impurities that affect melting point but are not handled well by any of these approaches. In order to determine the effect of impurities, a high temperature melting point furnace has been built in our laboratory. Melting points of over 50 real compositions have been measured. Obtained results have been correlated with chemical analysis data, including both main components and impurities. Modified coefficients for the empirical model have been determined and are presented.

2:50 PM Break

3:30 PM

Trace Element Control in Binary Ni-25Cr and Ternary Ni-30Co-30Cr Master Alloy Castings: Martin Detrois¹; Paul Jablonski¹; ¹US Department of Energy

Electro-slag remelting (ESR) is used for control of unwanted elements in commercial alloys. This study focuses on master alloys of Ni-25Cr and Ni-30Co-30Cr, processed through a combination of vacuum induction melting (VIM) and electro-slag remelting (ESR). Minor additions were made to control tramp element levels and modify the melting characteristics. Nitrogen and sulfur levels below 10 ppm and oxygen levels below 100 ppm were obtained in the final products. The role of the alloy additions in lowering the tramp element content, the resulting residual inclusions and the melting characteristics were determined computationally and confirmed experimentally. Additions of titanium were beneficial to the control of oxygen levels during VIM and nitrogen levels during ESR. Aluminum additions helped to control oxygen levels during remelting, however, aluminum pickup occurred when excess titanium was present during ESR. The usefulness of these master alloys for use as experimental remelt stock will also be discussed.

3:50 PM

Improvement of the Carbide Morphologies by Controlling Metal Pool Profile in the Electroslag Remelting Process of High Speed Steels: Li Wanming¹; Zhouhua JIANG²; Ximin ZANG¹; Xin DENG¹; Haiyang QI¹; Gang WANG¹; ¹University of Science and Technology Liaoning; ²Northeastern University

The carbide segregation of high speed steels is a bottleneck problem for producing large cross-section high speed steels. Electroslag remelting is a predominant method for preparing high-quality high speed steels, but the metal pool profile of conventional stationary-mould ESR restricts its ability to control carbide segregation. In order to control carbides segregation, a shallow and flat metal pool will be achieved by using secondary aerosol cooling and mould shunt effect to make the high speed steel rapid solidification. The metal pool profile in ESR process was obtained by tungsten powder detection and high speed steel carbide quality was evaluated. Effects of the secondary aerosol cooling and mould shunt effect on the temperature field of ESR process were analyzed through numerical simulation. Experimental results indicate that the electroslag remelting withdrawal process with secondary aerosol cooling technology and mould shunt effect can significantly decrease the depth of metal pool.

4:10 PM

Industrial-Scale Validation of a Transient Computational Model for Electro-Slag Remelting: Corey O'Connell¹; John deBarbadillo¹; David Evans¹; Ramesh Minisandram²; Richard Smith³; Jeffrey Yanke³; Eric Taleff⁴; Thomas Ivanoff⁴; Kanchan Kelkar⁵; William Hutchison⁶; Mark Benedict⁷; ¹Special Metals Corporation; ²ATI Specialty Materials; ³Carpenter Technology Corporation; ⁴The University of Texas at Austin; ⁵Innovative Research, LLC; ⁶GE Aviation; ⁷Air Force Research Laboratory

Under the auspices of the Metals Affordability Initiative (MAI), a collaborative team consisting of the U.S. Air Force, industry, software vendors, and academia was formed to produce and characterize commercial-sized ESR ingots for the purpose of validating a transient model of the ESR process. Trial melts for two rounds and one slab alloy 718 ingot were conducted, and the liquid metal pool was marked by nickel pellet additions to track its evolution. Full ingot cross-sections were evaluated by automated optical image acquisition, and image correlation techniques were used to estimate primary dendrite arm orientation and secondary dendrite arm spacing. The extent of chemical segregation was determined by X-ray fluorescence analysis at several locations within each ingot. Experimental results from the trials were used to benchmark the computational model in the commercial software package MeltFlow-ESR™.

4:30 PM

A Computational Model of the Electro-Slag Remelting Process with Power Interruption and Its Industrial Validation: Corey O'Connell¹; David Evans²; Kanchan Kelkar²; ¹Special Metals Corporation; ²Innovative Research, LLC

This paper presents a computational model for the analysis of an ESR process with power interruption and its application to industrial-scale processes. The model considers the electromagnetics, fluid flow, heat transfer, and phase change phenomena in the slag and ingot in five stages: 1) standard melting, 2) solidification of molten slag and metal pools during loss of power, 3) melting of the slag and ingot after power is recovered, 4) resumption of melting with the bulk of the slag not fully molten, and 5) resumption of standard melting. The model calculates the thermal history of the ingot during the entire process in a comprehensive manner. It has been applied to the analysis of industrial ESR processes for alloys 625 and 718. The results of the analyses illustrate the utility of the model for evaluating ingot quality when power is lost during the ESR process.

4:50 PM

The Sensitivity of an Electroslag Remelting Model to Uncertain Slag Properties: Alex Plotkowski¹; Matthew Krane²; ¹University of Tennessee - Knoxville and Purdue University; ²Purdue University

In the numerical models of electroslag remelting (ESR), the values of many input parameters, particularly slag thermophysical properties, have significant uncertainty. This study examines the impact of these uncertainties on simulation output and on model validation efforts. Probability distributions describing the uncertainties in the solid slag skin thermal conductivity and the liquid slag thermal conductivity, specific heat, and electrical conductivity are propagated through a model of ESR transport phenomena and solidification using a reduced-order surrogate model. The slag property uncertainties have a significant effect on the output probability distributions of steady state electrode melt rates and sump depths. These wide probability distributions limit model validation with experimental results and more detailed model development may be not improve the ability to simulate real processes without a strong simultaneous effort to improve the quality of property data.

Poster Session

Monday PM
September 11, 2017

Room: Poster Area
Location: The Hyatt at the Bellevue

Alloying Elements Loss Prevention and Surface Quality Improvement of As-cast Ingot Produced by Protective Atmosphere Drawing-Ingot-Type ESR: Cheng-bin Shi¹; ¹University of Science and Technology Beijing

To meet the demands in providing stable drawing-ingot operation and sound surface quality of as-cast ingot, as well as prevent alloying elements loss, a series of special slags were developed for drawn-ingot-type ESR. Meanwhile, the influence of melting rate on surface quality of ingot was clarified. The application of the developed slags was examined in industrial practice. Increasing SiO₂ addition strongly suppressed the crystallization, and reduced the liquidus temperatures of the slags. A small amount of SiO₂ addition in slag improved surface quality of as-cast ingot and stable drawing-ingot operation, and prevented silicon loss in H13 die steel during drawn-ingot-type ESR. Compared with other melting rates, the melting rate of 400kg/h brought sounder surface quality of as-cast ingot. At melting rate of 400kg/h, small amounts of TiO₂ and SiO₂ addition in slag not only strongly prevented Ti loss in 825 superalloy but also improved the surface quality of ingot.

New Approaches to the Control of Chemical Homogeneity of Electroslag Remelting Ingots: Leonid Levkov¹; Vladimir Dub¹; Dmitry Shurygin¹; ¹Public corporation Scientific and Production Association (CNIITMASH) A theoretical model of a molten slag as phase of variable stoichiometric composition and oxidation level (its parameter - equilibrium partial pressure of oxygen Po₂) was considered. Based on these ideas for management of oxygen content and components possessing high thermodynamic affinity content in the metal to it a new control method at electroslag remelting process was developed. The model of oxygen behavior during electroslag remelting was developed. This model takes into account characteristics totality of thermodynamic (chemical composition of metal,

input reductants, slag and its oxidation level) and kinetic (reaction surface of metal-slag interface, mass transfer rate in metal and slag). It's allows predicting the concentration of oxygen, aluminum, silicon and titanium in ingots. For the first time presented the results of implementation of industrial technologies with differentiated slag deoxidation in production of solid and hollow ingots (mass from 20kg to 60tons) from low-alloy, high-chromium and titanium-alloyed steels.

Numerical Simulation of Electroslag Composite Roll with Different Power Supply Circuit: Xin Deng¹; Yulong Cao; Ximin Zang; Zhouhua Jiang²; Wanming Li; Zhijun He; ¹University of Science and Technology Liaoning; ²Northeastern University

A new technology of electroslag remelting for the production of composite roll is proposed. A three-dimensional finite element model was developed to simulate the current density, voltage distribution and temperature field for the new technology. Especially, three kinds of power supply circuit are used in the numerical calculation of the model for electroslag composite roll, meanwhile, the skin effect is taken into account in electric field model by thermoelectric coupling method. Numerical results show that the double power supply circuit has better the ability of controlling current distribution, and the slag temperature distribution can be adjusted by adding a reactor in one of the circuits, the skin effect becomes strong and the maximum current occurs at the surface of electrode, the surface temperature of the core prior to cladding is mainly determined by the structure of power supply circuit and input power, the high temperature area of liquid slag pool varies with the power supply circuit.

Potentials of the Acid Slag for ESR: Stanislav Davidchenko¹; Ganna Stoopchenko²; Anatoliy Salnikov¹; Lev Medovar²; Igor Logozinski¹; Alexander Kuzmenko¹; ¹Dnepropetstal; ²Elmet-Roll; ³E.O. Paton Electric Welding Institute

Practice of the so known acid steel making processes has the really long history. There are many well known advantages of the acid steel making such as round shape non metallic inclusions or increased low cycle fatigue properties of acid Cr-Ni-Mo steel. Also known advantages and limitation of the acid ESR slag usage. Forecast of acid slag usage for the modern ESR practice to be given on the basis of the recent industrial tests with the different acid slag containing up to 70% SiO₂.

Refinement and Modification of Silicon Phases in Solidification of High Purity Hypereutectic Al-15Si Alloy: Kawther Al-Helal¹; Fan Zhongyun¹; Ian Stone¹; ¹Brunel University

Effect of phosphorus and calcium content on the morphology of silicon phases in solidification of different purity Al-15Si alloys was investigated. The micrographs show that typical microstructures of high purity consists of irregular coarse primary silicon particles with average particle size of approximately 68 μm dispersed in lamellar eutectic structure. While, typical microstructure of commercial purity consist of a perfect octahedron primary Si with average particle size of approximately 34 μm dispersed in fibrous eutectic structure. Adding 20 ppm P was quiet enough to refine primary silicon in high purity alloy and to reduce the average particle size to 20 μm. While, the same amount of P reduced the average particle size primary silicon in commercial purity alloy to 25 μm. Adding 30 ppm of Ca to the high purity modify the eutectic Si to a fibrous structure with shifting the eutectic position such that no primary silicon is evident.

Differences in Inclusion Morphology between ESR Remelted Steel With and Without Tracer in the Process Slag: Ewa Sjöqvist Persson¹; Alec Mitchell²; Pär Jönsson³; ¹Uddeholms AB; ²University of British Columbia; ³KTH Royal Institute of Technology

This study presents results on inclusion morphology in tool steels, intended to investigate inclusion behavior during ESR remelting. In order to optimize process routes for different steel grades, it is important to understand the origin of the inclusions in ESR materials. In a larger study comparison has been made between electrodes, ESR ingots of different ingot sizes and furnace types and conventional casted ingots. In this study ESR ingots from the same electrode heat have been remelted using a process slag with and without a tracer. The results explain the connection between the inclusions in the electrode, the inclusions in the ESR ingot and the process slag.

High Nitrogen Martensitic Stainless Steel 30Cr15Mo1N Manufactured by PIM-ESR Duplex Process: Hao Feng¹; Zhouhua Jiang¹; Huabing Li¹; Fubin Liu¹; Weichao Jiao¹; Yu Han¹; Hongchun Zhu¹; ¹Northeastern University

High nitrogen martensitic stainless steel (HNMS) has been paid extensive attentions due to its excellent performance. In this paper, 30Cr15Mo1N HNMS with nitrogen content higher than solubility at atmospheric pressure was manufactured by pressurized induction melting (PIM) and N₂-protective electroslag remelting (ESR) duplex process. Firstly, the 30Cr15Mo1N ingot was melted using PIM, and nitrogen alloying was carried out under high nitrogen pressure to obtain high nitrogen content (higher than 0.5 wt.%). Then, the ingot was remelted using ESR under N₂ atmosphere. Simultaneously, nitrogen was released because of the low nitrogen pressure during ESR. However, partial nitrogen was preserved owing to the relatively high remelting and solidification rate. The results indicated that the sulfur content was reduced efficiently, and inclusion distribution was improved greatly. And 30Cr15Mo1N HNMS (nitrogen content higher than 0.2 wt.%) with high hardness, toughness and corrosion resistance can be manufactured using PIM-ESR duplex process.

Inclusions, Microstructure and Carbides of D2 cold work die steel prepared under high pressure: changyong chen¹; zhouhua jiang¹; yang li¹; wei gong¹; cheng wang¹; ¹Northeastern University

The effect of pressure and magnesium on the solidification structure and primary carbides in D2 cold work die steel were investigated. The steel were smelting under high pressure from 0.5 MPa to 1.0 MPa with different magnesium. Results shows that the as-cast microstructure was greatly refined, and the network eutectic carbides in the as-cast steel were interrupted with the size reduced sharply at the same time. Furthermore, the transformation behavior and mechanism of carbides in forged and annealed steel was studied. The energy dispersive spectrometer, X-ray diffraction and the quantitative chemical examined method were carried. Meanwhile, the evolution of carbide under different temperatures and aging times were thermodynamically calculated by Thermo-Calc software. The results are as follows. The primary carbides and morphology, size and distribution are improved after the hot-forging operation. According to the calculated results, the carbides in the hot-forged and annealed steel are M7C3, M23C6 and M6C.

Study of Volume Deficit in Aluminium Alloy Casting: Laxminarayana Pappula¹; Syed Hussainy²; Viqar Mohiuddin²; Sundarajan Srinivasan³; ¹Osmania University; ²Muffakham Jah College of Engineering and Technology; ³Vishnu Educational Development and Innovation Center

Volume deficit in LM6, LM9 and LM24 cast aluminium alloy has been studied in the current presentation. The volume decreases during solidification and it leads to shrinkage defect. The influence of modulus of casting, orientation of casting in mould, shape of casting, riser aspect ratio, alloy, feed volume requirements and modulus extension factor has been studied on shrinkage defects. Casting yield studies and feeder safety margins are also studied. It is observed that volume deficit is sensitive to alloy, shape of casting, orientation of casting in mould and size of casting. The yield of casting is increased from 42% to 77% by using riser sleeves. The feed safety margins obtained are more than 15% the height of riser.

Study on Microstructure and Properties of Cast CB2 Steel of Different Co Content: Yu Lin Ma¹; Yue Liu²; Li Ping Zhang²; Xu Jiang²; Chun Ming Liu²; ¹Northeastern University; ²Northeastern University

The CB2 molten steel with different content of Co was smelted by IF induction furnace and cast into the shape of single cast test piece. The microstructures and mechanical properties of cast samples with different compositions were investigated by means of OM, SEM and tensile testing machine. The results show that the microstructure of the single cast test piece is uniform and the as-cast structure shows dendritic morphology. After heat treatment, the martensite morphology of the matrix replaces the dendritic morphology after heat treatment. With the increase of the content of Co, the amount of d-Fe in the sample matrix decreases, and after the Co content reaches 1.5%, the d-Fe disappears completely; By comparing the mechanical properties at room temperature, it can be concluded that when the Co content is 1.5% -2.0%, the comprehensive performance is better.

A 2D Transient Model for the Multiphase Flow, Heat Transfer in Electroslag Remelting Process with Different Fill Ratio: Jia Yu¹; Fubin Liu²; Zhouhua Jiang²; Kui Chen²; Huabing Li²; Xin Geng²; Yanwu Dong²; ¹northeastern university; ²northeastern university

A 2D axisymmetry transient model is established to simulate the fluid flow, heat transfer and the impact of fill ratios in electroslag remelting process with the same power input. The governing equations are discretized with the finite volume method and solved simultaneously. The motion of phase interface is tracked by the volume of fluid approach. The solidification is addressed by the enthalpy-porosity model. The simulation results indicate that the highest temperature is located below the edge of the electrode, and the superheat in metal pool is approximately 151 K. Two distinctly different vortexes within the slag bath promote the temperature field more uniform. During a period of droplet dripping, the first droplet entering the metal pool takes approximately 0.98s. Besides, the maximum value of electromagnetic field variables decreases with the fill ratio increasing, meanwhile, the zone occupied by the counter-clockwise flow in slag expands as well.

Considerations for the Operation of a Small Scale ESR Furnace: Paul Jablonski¹; Marion Cretu²; John Nauman²; ¹US Department of Energy; ²Consarc Corporation

Vacuum induction melting (VIM), electro-slag remelting (ESR) and vacuum arc remelting (VAR) are all techniques used to make high quality ingots of complex chemistries. In some cases, all three are used, e.g., alloys for aerospace applications and increasingly those for fossil power applications under extreme conditions. As such, research on alloys of this class require access to a variety of melting capabilities. In this report we discuss our recent experiences with a laboratory scale (8in/450lb) combination VAR/ESR furnace. The focus will be on the ESR operation, especially startup, since this is the most difficult operation in our experience. The complication arises from the necessity of the two-melt-mode design which prevents the use of a clamped base plate. Base plate lifting can result in excess arcing and subsequent copper pickup from the crucible bottom. Starting compact design, criteria for enabling the ram drive, and experiences with differing alloys will be discussed.

Design of ESR Slags According to Requested Physical Properties. Part 3: Surface Tension: Krzysztof Wroblewski¹; James Fraley¹; Jerry Fields¹; Brent DiBiaso¹; Stuart Rudoler¹; ¹American Flux & Metal LLC

In order to take full advantage of electroslag remelting, it is necessary to optimize the most important properties such as structure, chemical uniformity, and inclusion control by careful choice of remelt parameters and flux chemistry. Surface tension of molten slag controls the size of metal droplets formed in the process, which strongly affects chemical and thermal interaction between molten metal and slag. The surface tension component of multifunction G defining all six component slags of requested properties has been defined. Proposed brute-force algorithm for solving multifunction G is capable of producing results in reasonable time. Obtained results are in good agreement with physical properties of slags commonly analyzed in our laboratory.

Determination of Fluoride Content in ESR Flux by 19F TD-NMR: Krzysztof Wroblewski¹; Paul Giannatempo²; Dennis Guralnick³; Carol Steinhauer¹; James Fraley¹; Jerry Fields¹; Stuart Rudoler¹; ¹American Flux & Metal LLC; ²Cosa Xentaur Corporation; ³Dana Scientific Co.

ESR flux is a fused mixture of calcium fluoride, lime, alumina, and other oxides which is used in metal refining to facilitate removal of impurities and prevention of oxide formation during production of high-quality alloys. Presently used analytical methods for measurement of fluorides in ESR flux are time consuming, and for this reason cannot be used for in-process applications. A quick method (less than 15 minutes, including sample preparation) for routine determination of fluoride contents using Time-Domain NMR has been developed. The method has been tested on several flux formulations and the results were as accurate and precise as those obtained using conventional technology.

Effect of Al-Mg Alloy Addition on the Cleanliness and Inclusions in H13 Die Steel during ESR Process: Hao Wang¹; Jing Li¹; Cheng-bin Shi¹; ¹University of Science and Technology Beijing

The effect of Al-Mg alloy addition on the cleanliness and inclusions during electroslag remelting of H13 die steel with two levels of oxygen content was investigated. The results show that the oxygen content pick-up and silicon loss of remelted ingot were avoided, and sulphur content was further decreased. After Al-Mg alloy addition during protective gas electroslag

remelting (P-ESR) process. The oxygen content of consumable electrode (15×10^{-6}) was invalid to be reduced. The oxygen content of consumable electrode (80×10^{-6}) was reduced to 40×10^{-6} after P-ESR process, the oxygen content could not be reduced further in the Al-Mg addition trial. CaS content of complex inclusions were decreased significantly after P-ESR process. The type of inclusions was not changed during P-ESR process with Al-Mg alloy addition, except the increase in the concentrations of CaS in individual inclusion.

Effect of Magnesium on the Cleanliness and Inclusions of Low Alloy Ultra-high Strength Steel: Gong Wei¹; Pang Sheng¹; Wan Wan¹; Li Yang; ¹Northeastern University, China

Based on the low alloy ultra-high strength steel, the effect of magnesium on the cleanliness and inclusions in steel is discussed. The experimental results show that the total oxygen content in steel is decreasing with the increasing of magnesium content in steel, which can be reduced from 0.0024% in contrast sample to 0.0004%. And with the magnesium was added into the steel, the quantity and average diameter of inclusions in steel are gradually decreased, furthermore, the average space between inclusions is enlarged. Mg can give priority to the metamorphoses of oxide inclusions in liquid steel and subsequently metamorphic sulfide inclusions. Then with the addition of magnesium, the magnesium content in inclusions is increasing. The inclusion composition changed the sequence of $Al_2O_3 \rightarrow MgO \cdot Al_2O_3 - MnS \rightarrow MgO \cdot Al_2O_3 - MgS - MnS \rightarrow MgO - MgS$.

ESR for Railroad Wheels and Rails: Ganna Polishko¹; Dmytro Kolomiets¹; Ganna Stovpchenko²; Lev Medovar¹; Eugen Pedchenko¹; ¹E.O. Paton Electric Welding Institute; ²Elmet-Roll

Limitation of the further increase of the railroad wheels and rails workability to be discussed. To be presented observation of the metallurgical quality of ESR rails and wheels metal in compare with the metallurgical quality of the routine railroad metal manufacturing. Possibilities to utilize ESR for railroad wheels and rails of the superior quality for most critical applications to be discussed as well. Technical and economical criteria of ESR utilization for high speed rail road to be formulated and analyzed.

Experimental and Simulation Studies on Temperature Distribution of Manufacture Bimetallic Composite Material by Liquid-solid Bonding Method: Yulong Cao¹; Yanwu Dong¹; Zhouhua Jiang¹; Zhongtang Cheng¹; Fubin Liu¹; Xin Geng¹; ¹Northeastern University

Bimetallic composite materials have been given more and more attention because of their superiority in playing the advantages performance of the internal and external materials at the same time. In the study, a high chromium cast steel/carbon steel bimetallic composite material was fabricated by liquid-slag bonding method. In this experiment liquid metal of high chromium cast steel melted by VIM was casting into a cylindrical cast iron mold with a carbon steel bar in the center. A numerical model was built to predict the temperature distribution along the high chromium cast steel/carbon steel interface in real time by using the birth and death elements. Validation of the numerical model was conducted experimentally by measuring the temperature of the carbon steel and molds at some study points during the pouring and solidification process by thermocouples. A good agreement between the numerical and experimental results has been obtained.

Static Casting

Tuesday AM
September 12, 2017

Room: Grand Ballroom
Location: The Hyatt at the Bellevue

8:15 AM Introductory Comments

8:20 AM

Investigation on the Solidification Behavior and Microstructure of Superalloy Inconel 718 Prepared by Permanent Mold Casting: Yahui Liu¹; Maodong Kang¹; Yun Wu¹; Junwei Yu¹; Shuxian He¹; Jun Wang¹; ¹Shanghai Jiao Tong University

Continuous improvement of the engine operating temperature requires more excellent superalloys. A new method was investigated to improve the microstructure of polycrystalline superalloy by permanent mold casting. Physical experiment and numerical simulation were employed to understand the relationship between cooling condition and microstructure

evolution. The results revealed the significant refinement of grain and precipitation in the entire casting. Both the large cooling rate and thin-walled structure caused the small scale of dendritic secondary arm spacing and precipitation. Fine precipitates on grain boundaries (GBs) promoted the serrated GBs while developed precipitates promoted smooth GBs. Niobium segregation resulted in tiny MC carbide and Laves, but not acicular δ . The coating was trapped in casting to form surface layer while the carbon diffusion from iron mold to casting formed the subsurface carbon-rich layer.

8:40 AM

Interdendritic-melt Solidification Control Technique and Its Influence on the Porosity Reducing and Stress Rupture Life at intermediate temperature of a Ni-base Superalloy: Liang Zheng¹; Guoqing Zhang¹; Dominik Daisenberger²; Zhou Li¹; Chengbo Xiao¹; ¹Beijing Institute of Aeronautical Materials; ²Diamond Light Source

The interdendritic-melt solidification control (IMSC) technique was developed to manufacture equiaxed superalloy in order to reducing porosity of castings. The effect of IMSC process on the micro-porosities and stress rupture properties at $760^\circ/662\text{MPa}$ of IN792 alloy was investigated compared with conventional investment casting (CC). The microstructure and minor phases of alloys were characterized by optical metallography and synchrotron XRD. In addition, the fracture surfaces of stress ruptured IMSC and CC test bars were observed by scanning electron microscopy. The results indicate that the large size MC carbides, brittle plate-like η phase and large amount of porosity existed on the fracture surface of fast withdrawal rate IMSC alloy which result in low stress rupture life of the alloy. However, proper process parameter of IMSC can produce castings with much reduced porosity, equivalent stress rupture properties at intermediate temperature and higher stress rupture life at elevated temperature compared to conventional investment casting.

9:00 AM

Microstructure Evolution during the Stir Casting of a Graphene-Magnesium Alloy Composite: Pavan Penumakala¹; Gokul Nanda¹; Sujith Ravindran¹; Suresh Kurra¹; ¹BITS Pilani- Hyderabad Campus

Magnesium alloys are extensively used in automotive applications because of low density. However, their mechanical strength is lower compared to other lightweight materials. In recent times, graphene is used as an ideal reinforcement for increasing the strength of these alloys. In this present study, a composite material is fabricated using stir-casting method by reinforcing graphene in a magnesium alloy. The graphene particles are introduced into the molten magnesium alloy and stirred using a mechanical stirrer under argon atmosphere and allowed to solidify in a crucible. The grain size and the graphene distribution of the as-cast sample is examined using scanning electron microscope. The grain refinement if any, when compared to the pure magnesium alloy is also examined. Numerical simulations are carried out to find the parameters that influence the grain refinement and graphene distribution. The influence of process parameters such as particle size and the stirring speed is investigated.

9:20 AM

Evaporation of Cu and Sn in Ferrous Scrap Mixed with Hot Metal: Fahmi Tafwidli¹; Sung-Hoon Jung¹; Youn-Bae Kang¹; ¹Pohang University of Science and Technology

Cu and Sn are known as typical tramp elements in ferrous scrap which cause degradation of steel properties during hot processing. As a method to remove Cu and Sn from liquid iron melts, in the present study, Cu and Sn evaporation from liquid Fe-C-S alloys representing hot metal mixed with ferrous scrap was elaborated. In the regime of chemical reaction at the surface as a rate controlling step, a series of kinetic investigation were carried out in order to elucidate evaporation reaction mechanism by employing gas-liquid reaction in levitation/semi-levitation technique. A wider C content (0 to C saturation) and a wide temperature range from 1240 to 1500 °C were employed. Experimental results showed that increase of temperature and C content increased the evaporation rate. A kinetic model was developed, and it is shown that the newly developed model could explain the newly obtained experimental data obtained in the present study.

9:40 AM

A New Technology for Large Scale Electromagnetic Levitation Melting and Casting of Metals. Part I: Simulation: Sergejs Spitans¹; Henrik Franz¹; Egbert Baake²; ¹ALD Vacuum Technologies GmbH; ²Institute of

(TiAl) used for low pressure turbine blades. To do so a full triple melt TiAl recycling route consisting of VIM, PESR & VAR was established at the IME. Even using ceramic crucibles in VIM it was possible to obtain a material which meets all specifications even the low limit for oxygen. This material can and will be directly reused for casting turbine blades.

11:40 AM

The Characteristics of TiAl Alloy Powders Fabricated by Cold Crucible Induction Melting and Argon Gas Atomization: *Na Liu*¹; ¹Beijing Institute of Aeronautical Materials

The fine spherical TiAl alloy powders were produced by argon gas atomization of PSI's HERMIGA atomizers based on cold wall crucible induction melting, technology. The process of melting and atomization were studied. During melting, a skull forms at the bottom and the wall so the molten charge is always contained in a solid skull of the same composition. The powder particle size distributions are normal distribution, the powder particles are almost perfectly spherical, the gas content of the powder is low, among which oxygen concentration shows an increase with decreasing particle size, nitrogen content is basically constant for all size fraction. The microstructure of the powder exhibits cellular image resulted from rapid solidification.

Index

A

Al-Helal, K 3

B

Baake, E 5, 6
Bai, X 1
Ballantyne, A 6
Bartosinski, M 8
Bellot, J 6, 8
Benedict, M 2
Biebricher, U 1, 2
Blanpain, B 8
Brenk, J 8
Budna, K 8

C

Cao, Y 3, 5
Carré, A 6
Castro-Cedeno, E 6
Chapelle, P 1
Chen, C 4
Cheng, Z 5
Chen, K 4
Chen, X 7
Cibula, M 1
Cretu, M 4

D

Daisenberger, D 5
Davidchenko, S 3
deBarbadillo, J 2
Delzant, P 1
Deng, X 2, 3
Detroit, M 2
DiBiaso, B 2, 4
Dong, Y 4, 5
Drew, R 8
Dub, V 2, 3
Dzombic, R 1

E

Eickhoff, M 1
Elliott, A 7
Evans, D 2, 3

F

Feng, H 4
Fields, J 2, 4
Fraley, J 2, 4
Franz, H 1, 2, 5, 6
Friedrich, B 7, 8
Fruehan, R 8

G

Gambone, M 1
Geng, X 4, 5, 8
Gerardin, S 6
Giammatteo, P 4
Gong, W 4
Gregurek, D 8
Guo, M 8
Guralnick, D 4

H

Han, Y 4
He, S 5
He, Z 3
Hoffmann, T 1
Huang, X 6
Hübner, G 8
Hussainy, S 4
Hutchison, W 2

I

Ivanoff, T 2
Ivanov, I 2

J

Jablonski, P 2, 4
Jardy, A 1, 6
Jiang, X 4
jiang, z 4
Jiang, z 8
Jiang, Z 1, 2, 3, 4, 5
Jiao, W 4
Jönsson, P 3, 8
Jourdan, J 1
Jung, S 5

K

Kang, M 5
Kang, Y 5
Karasev, A 8
Karimi Sibaki, E 7
Kaufhold, D 1
Kelkar, K 2, 3, 7
Kharicha, A 7
King, P 1
Kisselman, M 2
Klöwer, J 1
Kolomiets, D 5
Krane, M 3
Kurra, S 5
Kuzmenko, A 3

L

Levkov, L 2, 3
Li, B 6
Li, H 4
Li, J 4, 7

Link, R 1
Liu, C 4
Liu, F 4, 5, 8
Liu, N 9
Liu, X 1
Liu, Y 4, 5
Liu, Z 6
Li, W 2, 3
Li, X 6
Li, Y 4
Li, Z 5
Logozinski, I 3

M

Malfliet, A 8
Ma, Y 4
McLean, A 6
Medovar, L 3, 5
Miller, C 7
Millet, Y 1
Minisandram, R 2
Mitchell, A 3
Mohiuddin, V 4
Morche, C 1
Motoyasu, G 6
Mu, H 8

N

Nair, B 1
Nanda, G 5
Nauman, J 4, 7
Niu, R 6

O

O'Connell, C 2, 3, 7

P

Pappula, L 4
Patel, A 7
Pedchenko, E 5
Peng, I 8
Penumakala, P 5
Perez, C 8
Pfeifer, H 1, 7
Plotkowski, A 3
Polishko, G 5

Q

Qi, H 2

R

Ravindran, S 5
Ren, J 2
Ren, N 6
Roberts, R 7
Rotmann, B 8
Rückert, A 1, 7

Rudoler, S 2, 4

S

Salnikov, A 3
Sawaya, T 6
Scholz, H 2
Schubert, C 7
Schwenk, M 7
Shannon, G 1
Sheng, P 5
Shi, C 3, 4
Shurygin, D 2, 3
Sjöqvist Persson, E 3, 8
Smith, R 2
Soda, H 6
Spanring, A 8
Spiess, P 8
Spitans, S 1, 5, 6
Srinivasan, S 4
Steinhauser, C 2, 4
Stone, I 3
Stovpchenko, G 3, 5

T

Tafwidli, F 5
Taleff, E 2
Tewes, J 1
Tiefers, R 8

W

Wang, C 4
Wang, G 2
Wang, H 4
Wang, J 5
Wang, R 1
Wang, Z 7
Wanming, L 2
Wan, W 5
Ward, R 1
Webler, B 8
Wei, G 5
Wenzl, C 8
Wollants, P 8
Woodside, R 1
Wroblewski, K 2, 4
Wu, J 7
Wu, M 7
Wu, Y 5

X

Xiao, C 5

Y

Yang, L 5
Yanke, J 2
Yan, P 7
Yuan, X 7
Yu, J 4, 5

Z

Zang, X 2, 3
Zeng, Q 7
Zhang, G 5
Zhang, L 4
Zhang, Y 1
Zheng, L 5, 8
Zhongyun, F 3
Zhu, H 4